



Your most recent listing is shown below. Please review this information and report any inaccuracies to the UL Engineering staff member who handled your Assignment.

JDYX January 21, 1992  
Fuses, Miscellaneous, Miniature, and Micro

POSSING ELECTRONIC CO LTD , TAIPEI TAIWAN E118177 (R)

Miniature cartridge enclosed, nonrenewable:			
Type or Cat. No.	Size	Amps	Volts, AC
Cat. No. GMA	5 (x) 20 MM	0.1-5	250
Cat. No. AGC	1/4 (x) 1-1/4 in.	0.1-7.25	250
Cat. No. GMP*	5 (x) 20 MM	0.1-5	250
Cat. No. GJV*	1/4 (x) 1-1/4 in.	0.1-7.25	250

\*Tight leads.

NO 3 ALLEY 2 LANE 305, JONG HO RD YUNG HO COUNTRY  
LOOK FOR LISTING MARK ON PRODUCT

Replaces E118177 dated November 21, 1991.  
214272001 H0727 Underwriters Laboratories Inc.®

F11/0201986  
208

For information on placing an order for UL Listing Cards in a 3 x 5 inch card format, please refer to the enclosed ordering information.

UNDERWRITERS LABORATORIES INC.

An independent, not-for-profit organization testing for public safety

333 1/2 Houston Road  
Brook, Illinois 60062-2096, USA  
708/272-8800  
Telex: 6502543343  
FAX No. (708) 272-8129

1285 Walt Whitman Road  
Melville, L.I., New York 11747-3031, USA  
516/271-6200  
Telex: 6852015  
FAX No. (516) 271-8258

1655 Scott Blvd.  
Santa Clara, California 95050-4169, USA.  
408/535-2400  
Telex: 184219  
FAX No. (408) 296-3256

12 Laboratory Drive  
P.O. Box 11995  
Research Triangle Park,  
North Carolina 27701-2095,  
919/549-1400  
Telex: 493752R  
FAX No. (919) 515-1042

The company named below has been authorized by CSA to represent the products listed in this record as "CSA Certified" and to affix the CSA Mark to these products according to the terms and conditions of the CSA Service Agreement and applicable CSA program requirements (including additional Markings).

File No: 089571 0 000

Class No: 1422 01 FUSES Special Type

## SUBMITTOR

4561703

## FACTORY

4561703

January 28, 2003 (Replaces: April 2, 1992)

Supplemental, glass cartridge fuses, non-renewable:

- Cat No AGC rated 100mA-7.25A, 250V ac, IR 125-10 kA, IR 250-\*, 6.35mm by 31.75mm.
- Cat No GMP (pigtail) and GMA rated 100mA-5A, 250V ac, IR 125-10 kA, IR 250-\*, 5.2mm by 20mm.

\*Note: Types with IR 250-\* have interrupting ratings of 35A for 1A or less, 100A for more than 1A to 3.5A, 200A for more than 3.5A to 7.25A, as applicable for the ampere ratings listed.

/gj