

18W (3 ~ 24V) AC-DC SWITCHING ADAPTOR

Model	Output Rating	Tol.	R&N	Pmax.
JLD-05030	5V/3.0A	5%	50mV	15W
JLD-12015	12V/1.50A	3%	100mV	18W
JLD-15012	15V/1.20A	3%	100mV	18W
JLD-24007	24V/0.75A	3%	120mV	18W

其它規格可訂製

FEATURE

- Compact size , light weight
- Over load protection
- DC output plug option
- Short circuit protection
- Low cost / high reliability
- 100% full load burn-in test
- 1 year warranty



美規

78 x 30 x 46 mm

歐規

ELECTRICAL SPECIFICATIONS

Input

Input range----- 100 – 240VAC(Full Range) , 47 – 63Hz
Input current (rms)--- 160mA @ 90VAC; 80mA @ 260VAC MAX..
Efficiency ----- >70% @ full load, 115VAC (DC Conversion)

SAFETY

CE FCC TUV UL

Output

Voltage (Vo) ----- +3V ~ +24V
Voltage regulation --- ±8% @ constant voltage mode
Current limit ----- ±8% @ constant current mode
Maximum power (Po) ----- 18W 
Length of output cable --- 150 cm , AWG 20 X 2C
Standard plug of DC output - - - - As your instruction

ENVIRONMENTAL

Operating temperature----- 0°C to +50 °C ambient
Storage temperature ----- -10 °C to +70 °C
Humidity ----- 20% ~ 90% RH