

太陽能電池規格一覽表(室 外)

型 號	尺寸 ， 毫米			電 性		環境 條件	備 註	
	Type	Model	長	寬	厚度			Vop, V
SC 5030		50.00	29.00	2.00	1.8	26.0	C	
SC 5848		57.80	48.20	2.00	8.0	8.0	C	
SC 7035		70.20	35.00	2.00	4.0	18.0	C	
SC 9728		96.80	28.00	2.00	6.0	15.0	C	
SC 12439		124.50	39.30	2.00	15.0	12.0	C	
SC 14633		145.70	32.50	2.00	9.6	13.0	C	
SP 0611/SC 60110 AZ		110.00	60.00	2.35	2.5	88.0	C	
SP 0907/SC 9070 AZ		89.70	69.70	2.35	4.0	50.0	C	
SP 1515/SC 150150AZ		150.00	150.00	2.35	7.5	120.0	C	
SP 3007/SC 29574AZ		295.00	74.00	2.35	14.5	55.0	C	
SP 3030/SC 305305AZ		304.80	304.80	2.35	17.0	177.0	C	
SM 5120		30.00	60.00	5.20	0.5	280.0	C	
SM 5626		30.00	57.00	5.20	3.0	60.0	C	
SM 8656		86.00	56.00	5.20	3.0	120.0	C	
SM 1143		108.00	43.00	3.00	9.0	30.0	C	
SM 9063		92.00	63.00	3.00	9.0	50.0	C	
SM 5151		60.00	65.00	5.20	4.0	75.0	C	
SM 5055		60.00	65.00	5.20	2.5	150.0	C	
SM 1520		115.00	58.00	5.20	7.5	100.0	C	
SM 1158		115.00	58.00	5.20	1.0	800.0	C	
SM 1607		160.00	68.00	8.00	3.0	460.0	C	Power Module
SM 1414		135.00	135.00	3.60	0.5	4800	C	Power Module
SM 3015		118.00	176.00	8.00	14.5	120.0	C	Power Module
SM 1530		118.00	176.00	8.00	7.5	200.0	C	Power Module
SM 1611		135.00	135.00	8.00	3.0	800.0	C	Power Module
SM 3412		346.00	120.00	16.00	6.0	800.0	C	Power Module
SM 3544		365.00	450.00	35.00	14.5	1000	C	Power Module
SM 4340		436.00	406.00	33.00	14.5	1200	C	Power Module
SM 5640		564.00	406.00	33.00	14.5	1600	C	Power Module
SM 8140		816.00	406.00	33.00	14.5	2400	C	Power Module

備註 (1) a : FI 200 Luxs , 25°C b : FL 300 Luxs , 25°C c : AM1(100mW/cm) , 25°C

(2) 其它尺寸可依客戶需求作特殊設計

(3) SC、SP 係非晶系列，SM 係單晶系列