

# TRF-V/TRF-V2

	<b>OFF DELAY RELAY</b>	<b>斷電延遲繼電器</b>
--	------------------------	----------------



- CE Approved .
- MOTOROLA IC inside.
- The large time is 10minutes .
- 德國 CE 認證。
- 使用美國 MOTOROLA IC 。
- 最大之斷電延遲時間為 10M。
- 具有兩組接點之 TRF-V2。

## ORDERING INFORMATION 訂購說明

Ex    TRF    V                      60S                      A220

Controller Type 型式	Time range 時間範圍				Operating voltage 電壓範圍	
V : TRF-V V2 : TRF-V2	1S	0.1S TO 1S	60S	6S TO 60S	D12: DC12V	D24: DC24V D48: DC48V A12: AC12V A24: AC24V A110: AC110V A220: AC220V A240: AC240V A380: AC380V A440: AC440V
	6S	0.6S TO 6S	3M	10S TO 3M		
	10S	1S TO 10S	6M	10S TO 6M		
	30S	3S TO 30S	10M	20S TO 10M		

## SPECIFICATIONS & CHARACTERISTICS 規格 & 特性

Type 型式	TRF-V	TRF-V2
Rate operation voltage 額定電壓	DC:12V/ 24V/ 48V AC:12V/ 24V/ 110V/ 220V/ 240V/ 380V/ 440V	
Operating voltage range 電壓使用範圍	DC: 85%~110% AC: 80%~110%	
Rated frequency 額定頻率	AC: 50~60Hz	
Rated power consumption 額定功率消耗	About: 2VA	
Rated control capacity 輸出容量	AC: 3A 250VAC P.F.=1	AC: 2A 250VAC P.F.=1
Setting accuracy 設定誤差	± 10%	
Reset time 復歸時間	Less than 0.1S	
Life 壽命	Mechanical 機械	
	Electrical 電氣	
Output arrangement 輸出方式	Time out 1 form C	Time out 2 form C
Max. temperature rise 最大溫升	55 deg.	
Ambient temperature 周圍溫度	-10 to +65 但不結冰結露 But no ice	
Ambient humidity 周圍溼度	Max. 85% RH	
Weight 重量	About 170g	