



廠牌 Brand	STANDEX	STANDEX	STANDEX	PIC	ALEPH
型號 Switch Type	GR-100	NL-126	GR-560 (彎腳型)	CRH-500	HYR-155
特性 Characteristics	通用型	高功率型	通用型	切換型	切換型
接點型式 Contact Form	A	A	A	C	C
接點材質 Contact Material	Rh	Rh	Rh	Rh	Rh
功率 Power Rating(高AT值)	10W	50W	10W	30W	—
切換電流 Switch Current AC/DC(A)	1	1.5	1	0.5	0.25
切換電壓 Switch Voltage(max · VDC)	100	200	100	500	100
切換電壓 Switch Voltage(max · VAC)	150	150	125	300	—
帶電流 Carry Current AC/DC(A)	1.5	2.5	1.5	3.0	0.5
崩潰電壓 Breakdown Voltage(max · VDC)20AT以上	250	250	200	1200	200
接觸電阻 Contact Resistance(Ohms)	0.1	0.1	0.1	0.13	0.2
絕緣阻抗 Insulation Resistance(Ohms)	10^{12}	10^{12}	10^{12}	10^9	10^9
感動時間 Operate Time(ms)	0.8	0.8	0.6	4.5	—
釋放時間 Release Time(ms)	0.1	0.1	0.1	7.0	—
響應頻率 Resonant Freq(kHz)	2.2	2.2	3.0	2.8	—
感動值 Pull-in Range (AT)	10-45	20-50	10-45	50-80	15-50
接觸電容 Contact Capacitance(max pf)	0.2	0.2	0.2	2	0.8
運轉溫度 Operate Temperature	-40~ +150	-40~ +150	-40~ +150	-20~ +125	—
玻璃管長度 Glass Length(max.mm)	14.2	14.2	14.2	39.7	14.3
玻璃管直徑 Glass Diameter(max.mm)	2.5	2.5	2.3	5.55	2.6
總長 Overall Length(max.mm)	54	54	54	85.7	52.6
兩端線徑 Lead Diameter(max.mm)	0.6	0.6	0.6	—	—